



KONICA MINOLTA

AccurioPrint  
C4065

# BUILD YOUR BRIDGE TO SUCCESS

## ACCURIOPRINT C4065



### RETHINK VERSATILITY

Introducing the AccurioPrint C4065 – the incredibly versatile digital printer that connects you with success. The outstanding image and color quality, media versatility, and fast 65 color ppm or 80 black & white ppm output make this press a high-value, yet cost-effective solution for print professionals.

# ACCURIOPRINT C4065

# SPECIFICATIONS

## RETHINK OPTIONS

### SYSTEM SPECIFICATIONS

Resolution	3,600 (equivalent) x 2,400 dpi x 8 bit
Paper weight	62 – 360 g/m <sup>2</sup>
Paper sizes	330.2 x 487.7 mm 330.2 x 862 mm (max. duplex) 330.2 x 1300 mm (max. simplex)
Paper input	Max.: 7,380 sheets
Dimension (WxDxH)	31.49" x 35.55" x 42.36"
Unit weight	696.66 lb.

### PRODUCTIVITY

#### AccurioPrint C4065

8.5 x 11 – max. per minute	65 ppm
11 x 17 – max. per minute	36 ppm

#### KONICA MINOLTA IMAGE CONTROLLER IC-607

Architecture	Internal
OS	Linux
CPU	Intel Pentium C4400
Clock speed	3.3 GHz
RAM std	16 GB
HDD	2 TB (2 x 1TB)
Page-description language	Adobe PostScript 3; PDF v1.7; TIFF (v6); PPML v2.2
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

#### FIERY IMAGE CONTROLLER IC-419

Architecture	Internal
OS	Linux
CPU	Intel® Pentium® Processor G4400
Clock speed	3.3 GHz
RAM std	8 GB
HDD	500 GB
Page-description language	Adobe® PostScript® Levels 1, 2, 3, APPE 5, Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, pub (via Hot Folders)
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

### OPTIONS

KM Image Controller	IC-607
EFI internal Controller	IC-419
Paper Feeding Unit	PF-602m
Dehumidifier heater	HT-504
Paper feeding unit	PF-707m
Dehumidifier heater	HT-506
PFU connection Kit	FA-502
Large capacity feeding unit	LU-202m
Dehumidifier heater f. LU	HT-503
Envelop printing guidef. LU	MK-746
Large capacity feeding unit (banner)	LU-202XLm
Multi bypass feeding	MB-508
Banner Paper Feeder kit	MK-760
Multi bypass tray	MB-509
Intelligent Media Sensor	IM-101
Output Tray	OT-511
Stapling Unit	FS-532m
Saddle Stitcher Kit	SD-510
Punch Kit	PK-525
Post Inserter Kit	PI-502
Output Tray Unit	OT-512
Long Sheet Kit (Output)	MK-761

#### DF-713 — DUAL SCAN DOCUMENT FEEDER (OPTION)

Tray Capacity	300 sheets (80 gsm)		
Original Weight Duplex	50 – 210 gsm		
Detectable Document Size	Min: 3.94" x 5.51" (100 x 140 mm) Max: 11.69" x 17" (297 x 431.8 mm)		
Scan Speed by Resolution	200 dpi	Color: Simplex 140 ipm Monochrome: Simplex 140 ipm	Duplex 280 ipm Duplex 280 ipm
	300 dpi	Color: Simplex 120 ipm Monochrome: Simplex 120 ipm	Duplex 240 ipm Duplex 240 ipm
	400 dpi	Color: Simplex 100 ipm Monochrome: Simplex 100 ipm	Duplex 200 ipm Duplex 200 ipm
Copy Speed	600 dpi	Color: Simplex 75 ipm	Duplex 150 ipm
		Monochrome: Simplex 80 ipm	Duplex 160 ipm

- All specifications refer to A4-size paper of 80 gsm quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

**RETHINK  
PRINT**

Learn more at  
**ReThinkPrint.com**

© 2020 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA and the KONICA MINOLTA logo are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.  
100 Williams Drive, Ramsey, New Jersey 07446

**CountOnKonicaMinolta.com**



Item: C4065SS  
11/20-1